

SEACAT SCHMEDING

EQUIPMENT TABLE FROM "LLOYDS REGISTER OF SHIPPING"

Equipment number Exceeding - Not Exceeding	Equipment letter	Stockless Bower Anchors		Stud-link Chain Cables		
		Number	Mass per anchor	Total length m	Diameter and steel grade	
			kgs		U2 mm	U3 mm
50-70	A	2	180	220	12,5	
70-90	B	2	240	220	14	
90-110	C	2	300	247,5	16	
110-130	D	2	360	247,5	17,5	
130-150	E	2	420	275	17,5	
150-175	F	2	480	275	19	
175-205	G	2	570	302,5	20,5	
205-240	H	2	660	302,5	22	20,5
240-280	I	2	780	330	24	22
280-320	J	2	900	357,5	26	24
320-360	K	2	1020	357,5	28	24
360-400	L	2	1140	385	30	26
400-450	M	2	1290	385	32	28
450-500	N	2	1440	412,5	34	30
500-550	O	2	1590	412,5	34	30
550-600	P	2	1740	440	36	32
600-660	Q	2	1920	440	38	34
660-720	R	2	2100	440	40	36
720-780	S	2	2280	467,5	42	36
780-840	T	2	2460	467,5	44	38
840-910	U	2	2640	467,5	46	40
910-980	V	2	2850	495	48	42
980-1060	W	2	3060	495	50	44
1060-1140	X	2	3300	495	50	46
1140-1220	Y	2	3540	522,5	52	46
1220-1300	Z	2	3780	522,5	54	48
1300-1390	A+	2	4050	522,5	56	50
1390-1480	B+	2	4320	550	58	50
1480-1570	C+	2	4590	550	60	52
1570-1670	D+	2	4890	550	62	54
1670-1790	E+	2	5250	577,5	64	56
1790-1930	F+	2	5610	577,5	66	58
1930-2000	G	2	6000	577,5	68	60

2230-2380	I+	2	6900	605	73	64
2380-2530	J+	2	7350	605	76	66
2530-2700	K+	2	7800	632,5	78	68
2700-2870	L+	2	8300	632,5	81	70
2870-3040	M+	2	8700	632,5	84	73
3040-3210	N+	2	9300	660	84	76
3210-3400	O+	2	9900	660	87	78
3400-3600	P+	2	10500	660	90	78
3600-3800	Q+	2	11100	687,5	92	81
3800-4000	R+	2	11700	687,5	95	84
4000-4200	S+	2	12300	687,5	97	87
4200-4400	T+	2	12900	715	100	87
4400-4600	U+	2	13500	715	102	90
4600-4800	V+	2	14100	715	105	92
4800-5000	W+	2	14700	742,5	107	95
5000-5200	X+	2	15400	742,5	111	97
5200-5500	Y+	2	16100	742,5	111	97
5500-5800	Z+	2	16900	742,5	114	100
5800-6100	A*	2	17800	742,5	117	102
6100-6500	B*	2	18800	742,5	120	107
6500-6900	C*	2	20000	770	124	111
6900-7400	D*	2	21500	770	127	114
7400-7900	E*	2	23000	770	132	117
7900-8400	F*	2	24500	770	137	122
8400-8900	G*	2	26000	770	142	127
8900-9400	H*	2	27500	770	147	132
9400-10000	I*	2	29000	770	152	132
10000-10700	J*	2	31000	770	157	137
10700-11500	K*	2	33000	770	157	142
11500-12400	L*	2	35500	770	162	147
12400-13400	M*	2	38500	770		152
13400-14600	N*	2	42000	770		157
14600-16000	O*	2	46000	770		162

SEACAT-Schmeding can not be hold responsible for any misprinting or etc. in above table.